

# UTV CAB ENCLOSURE INSTALLATION REQUIREMENTS

**\*\*PLEASE READ PRIOR TO PURCHASING YOUR UTV CAB ENCLOSURE\*\***

**For a successful installation please adhere to the following requirements:**

1. **INSTALLED ACCESSORIES – IMPORTANT!** If you have other accessories installed on your vehicle that interfere with the installation of the enclosure, you must remove them prior to and during the use of the enclosure. Some common items that may cause interference are hard top roofs, windshields, rear windows, spotlights, brackets, speakers and all other items mounted on the exterior portion of the roll cage.
2. **SHARP EDGES** – It is the installer's responsibility to protect the cab enclosure from all sharp edges that may exist on the vehicle. Failure to do so may result in avoidable damage to the cab enclosure and voiding the manufacturer's warranty.
3. **TEMPERATURE** – Install the enclosure when the vehicle, the enclosure and the ambient temperature are near 70° Fahrenheit for several hours prior to installation. This will ensure that the material is flexible enough to stretch slightly during installation; making it easier to install and resulting in a professional appearance.
4. **FINISHED APPEARANCE** – Ensure that the finished installation results in a tight fitting enclosure. By design, the enclosure should be smooth over the roll cage/vehicle after installation. This will eliminate unnecessary noise and abrasive contact from the material as wind moves around the enclosure.
5. **WRINKLES & CREASES** – It may be necessary for you to remove some wrinkles or creases from the vinyl windows after installation. During the packaging process at the factory, the vinyl windows may incur wrinkles or creases which obscure visibility. **Please follow the procedure in the installation instructions provided with your enclosure to remove the wrinkles and/or creases from the windshield.**



Here's an idea! We have many customers who purchase our enclosures with the direct intention of removing the (soft) vinyl windshield from it. They are doing this because they already have, or plan to purchase a (hard) Lexan® type windshield for their vehicle. They are using the roll of adhesive backed, hook-and-loop tape (similar to Velcro) that comes with our enclosure to attach the enclosure to their windshield. They tell us that it is the best of both worlds because they have the warmth, dryness and comfort of the enclosure and superior clarity through the Lexan type windshield. Note: Removal of the vinyl windshield may void the manufacturer's warranty.

6. **DISTORTION & OBSCURED VISIBILITY** – Due to the nature of the material used in manufacturing the vinyl portion of the windows, some distortion is inevitable however; excessive distortion to the point of obscured visibility should be reported to us. We will then provide a replacement to you at no cost, and/or set up return authorization for the one you have.



**Things Sought After**

"Everybody is searching for something"